

| Model                       |                     |                   | MI-15Q4/DHN1-A3 | MI-22Q4/DHN1-A3            | MI-28Q4/DHN1-A3 | MI-36Q4/DHN1-A3 | MI-45Q4/DHN1-A3 |
|-----------------------------|---------------------|-------------------|-----------------|----------------------------|-----------------|-----------------|-----------------|
| Power supply                |                     |                   |                 | 1-phase,220-240V,50/60Hz   |                 |                 |                 |
| Capacity                    | Cooling             | kW                | 1.5             | 2.2                        | 2.8             | 3.6             | 4.5             |
|                             | Heating             | kW                | 1.7             | 2.4                        | 3.2             | 4.0             | 5.0             |
| Power input                 | Cooling             | W                 | 14              | 15                         | 16              | 21              | 21              |
|                             | Heating             | W                 | 11              | 13                         | 13              | 18              | 18              |
| Airflow rate(H/M/L)         |                     | m <sup>3</sup> /h | 526/449/364     | 526/449/364                | 576/503/405     | 604/516/400     | 604/516/400     |
| Sound pressure level(H/M/L) |                     | dB(A)             | 33.9/32.5/21.8  | 34.8/32.4/22.4             | 34.8/32.4/22.4  | 40.5/34.6/27.8  | 40.5/34.6/27.8  |
| Sound power level(H/M/L)    |                     | dB(A)             | 45/44/34        | 46/44/35                   | 46/44/35        | 52/47/41        | 52/47/41        |
| Main body                   | Net dim.(WxHxD)     | mm                | 570x260x570     | 570x260x570                | 570x260x570     | 570x260x570     | 570x260x570     |
|                             | Packing dim.(WxHxD) | mm                | 675x285x675     | 675x285x675                | 675x285x675     | 675x285x675     | 675x285x675     |
|                             | Net/gross weight    | kg                | 16/22           | 16/22                      | 16/22           | 17.5/23.5       | 17.5/23.5       |
| Panel                       | Net dim.(WxHxD)     | mm                | 647x50x647      | 647x50x647                 | 647x50x647      | 647x50x647      | 647x50x647      |
|                             | Packing dim.(WxHxD) | mm                | 715x123x715     | 715x123x715                | 715x123x715     | 715x123x715     | 715x123x715     |
|                             | Net/gross weight    | kg                | 2.5/4.5         | 2.5/4.5                    | 2.5/4.5         | 2.5/4.5         | 2.5/4.5         |
| Piping connections          | Liquid/gas pipe     | mm                | Φ6.35/Φ12.7     | Φ6.35/Φ12.7                | Φ6.35/Φ12.7     | Φ6.35/Φ12.7     | Φ6.35/Φ12.7     |
|                             | Drain pipe          | mm                | OD Φ25          | OD Φ25                     | OD Φ25          | OD Φ25          | OD Φ25          |
| Standard controller         |                     |                   |                 | Wireless remote controller |                 |                 |                 |