

Model			MI-15Q4/DHN1-A3	MI-22Q4/DHN1-A3	MI-28Q4/DHN1-A3	MI-36Q4/DHN1-A3	MI-45Q4/DHN1-A3
Power supply					1-phase,220-240V,50/60Hz		
Capacity	Cooling	kW	1.5	2.2	2.8	3.6	4.5
	Heating	kW	1.7	2.4	3.2	4.0	5.0
Power input	Cooling	W	14	15	16	21	21
	Heating	W	11	13	13	18	18
Airflow rate(H/M/L)		m <sup>3</sup> /h	526/449/364	526/449/364	576/503/405	604/516/400	604/516/400
Sound pressure level(H/M/L)		dB(A)	33.9/32.5/21.8	34.8/32.4/22.4	34.8/32.4/22.4	40.5/34.6/27.8	40.5/34.6/27.8
Sound power level(H/M/L)		dB(A)	45/44/34	46/44/35	46/44/35	52/47/41	52/47/41
Main body	Net dim.(WxHxD)	mm	570x260x570	570x260x570	570x260x570	570x260x570	570x260x570
	Packing dim.(WxHxD)	mm	675x285x675	675x285x675	675x285x675	675x285x675	675x285x675
	Net/gross weight	kg	16/22	16/22	16/22	17.5/23.5	17.5/23.5
Panel	Net dim.(WxHxD)	mm	647x50x647	647x50x647	647x50x647	647x50x647	647x50x647
	Packing dim.(WxHxD)	mm	715x123x715	715x123x715	715x123x715	715x123x715	715x123x715
	Net/gross weight	kg	2.5/4.5	2.5/4.5	2.5/4.5	2.5/4.5	2.5/4.5
Piping connections	Liquid/gas pipe	mm	Φ6.35/Φ12.7	Φ6.35/Φ12.7	Φ6.35/Φ12.7	Φ6.35/Φ12.7	Φ6.35/Φ12.7
	Drain pipe	mm	OD Φ25	OD Φ25	OD Φ25	OD Φ25	OD Φ25
Standard controller					Wireless remote controller		